

ITEM NUMBER: 508 - Extractor HUD 13  
VERSION 4 EFFECTIVE DATE: 10/03/01 SUPERCEDES: 3/12/01 PREPARED 1  
Section(s) Revised: HMIS, III, VI, IX  
IDENTITY (As Used On Label and List):

EMERGENCY MEDICAL Telephone# 1-866-836-8855 (24 Hrs) Outside of the U.S.A. Call 952-852-4646

PRODUCT HAZARD RATINGS (HMIS): - Health = 2, Fire = 2, Reactivity = 1, Protective Equipment = B  
(Rating Legend: - 4 = Extreme, 3 = Serious, 2 = Moderate, 1 = Slight, 0 = Minimal, \* = Chronic Hazard)

\*\*\*\*\* SECTION I \*\*\*\*\*

Hud Brite TELEPHONE NUMBER FOR INFORMATION ;  
Wildwood

DATE PRINTED : 9/07/05 NAME OF PREPARER : REGULATORY COMPLIANCE

PA 15091

\*\*\*\*\* SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION \*\*\*\*\*

Chemical Names	CAS #	SARA SEC 313	ACGIH TLV-TWA/STEL	OSHA PEL-TWA/STEL	% By Wt.
Diethylene glycol monobutyl ether	112-34-5	Yes	NE / NE	NE / NE	1-5
Liquefied petroleum gas mixture	See below	No	-- / --	-- / --	5-10
Propane	74-98-6	--	2500 ppm/ NE	NE / NE	-
n-Butane	106-97-8	--	800 ppm/ NE	NE / NE	-

Balance of ingredients are non-hazardous or below reportable levels.

\*\*\*\*\* SECTION III - PHYSICAL CHARACTERISTICS \*\*\*\*\*

Boiling Point: NA Vapor Pressure (psig): 110 @ 130F / 60 @ 70F Specific Gravity (H2O=1): 0.9503  
pH: 10.49 Solubility/Water: Moderate Vapor Density (AIR=1): ND Evaporation Rate (Ether=1): ND  
Appearance and Odor: Aerosol spray with fragrant odor.

\*\*\*\*\* SECTION IV - FIRE AND EXPLOSION HAZARD DATA \*\*\*\*\*

Aerosol Flammability: Product is not required to be labeled as flammable as described in 16 CFR 1500.3 and 1500.45.  
Flashpoint: <0F (Propellant); None even until boiling (Concentrate)  
Flammable Limits - % Volume In Air (Propellant): LEL: 1.9 UEL: 9.5  
Extinguishing Media: Carbon dioxide, water spray, foam, or dry chemical.  
Special Fire Fighting Procedures: Containers should be cooled with water to prevent vapor pressure build up.  
Use equipment or shielding, as required, to protect personnel from bursting, rupturing or venting containers.  
Unusual Fire and Explosion Hazards: Fire fighters and others who may be exposed to the products of combustion should be equipped with NIOSH-approved positive pressure self-contained breathing apparatus (SCBA) and full protection clothing. At elevated temperatures (over 54C-130F) containers exposed to direct flame or heat contact should be cooled with water to prevent weakening of container structure.

\*\*\*\*\* SECTION V - REACTIVITY DATA \*\*\*\*\*

Stability: Stable Hazardous Polymerization: NA  
Incompatibility (Materials to Avoid): None.  
Hazardous Decomposition Products: Carbon monoxide and hydrocarbon vapors.  
Conditions to Avoid: Keep away from heat, sparks, and flames. Dropping of containers may cause bursting.

## \*-\*-\*-\*-\* SECTION VI - HEALTH HAZARD DATA

\*-\*-\*-\*-\*

Route(s) of Entry - Inhalation: X Eyes: X Skin: X Ingestion:  
 HAZARDS IDENTIFICATION: EYES: May cause moderate irritation. SKIN: Non-irritating. INHALATION: Not hazardous in normal industrial use. INGESTION: Not hazardous in normal industrial use.

CHRONIC EFFECTS/TARGET ORGANS: None known.

EMERGENCY AND FIRST AID PROCEDURES: EYES: Immediately flush with plenty of water for at least 15 minutes. Get prompt medical attention. SKIN: Wash with soap and plenty of water. INHALATION: Remove to fresh air. If symptoms develop, seek immediate medical attention. If not breathing, give artificial respiration. INGESTION: Get immediate medical attention. Do NOT induce vomiting unless directed by medical personnel. Never give anything by mouth to an unconscious person.

CARCINOGENICITY:

No regulated ingredients.

TOXICITY INFORMATION:

Diethylene glycol monobutyl ether:

LD50 Oral (Rat): 7292 mg/kg

LD50 Dermal (Rabbit): 2764 mg/kg

## \*-\*-\*-\*-\* SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

\*-\*-\*-\*-\*

Releases or Spills: Remove all sources of ignition and ventilate area. Soak up spill with an inert absorbent and place into a designated disposal container. Consult local regulatory agency for proper disposition of material.

Waste Disposal Method: Do not puncture or incinerate containers. When contents are depleted continue to depress button until all gas is expelled. Dispose of container in accordance with local, state, and federal regulations.

Handling And Storing: Avoid breathing vapor. Keep away from heat, sparks and flame. Use with adequate ventilation. Do not puncture or incinerate containers. Do not expose to direct sunlight or store at temperatures above 120F (48.9C). Store as Level 1 Aerosol (NFPA 30B).

Other Precautions: Please read and follow the directions on the product label; they are your best guide to using this product in the most effective way, and give the necessary safety precautions to protect your health.

## \*-\*-\*-\*-\* SECTION VIII - EMPLOYEE PROTECTION

\*-\*-\*-\*-\*

Respiratory Protection (Type): None required if good ventilation is maintained. If exposure exceeds occupational exposure limits (Sec. II), use a NIOSH approved respirator to prevent overexposure.

Ventilation: Local exhaust is adequate under normal conditions, mechanical ventilation is optional.

Protective Gloves: Chemical resistant gloves are recommended - consult glove manufacturer to determine the proper type for a specific operation.

Eye Protection: Safety glasses are recommended.

Other Protective Clothing or Equipment: Wear impervious clothing to prevent skin contact.

Work/Hygienic Practices: Ensure strict sanitary conditions are conformed to when working around chemicals. Protective clothing and equipment should be in accordance with 29 CFR 1910.132 and CFR 1910.133.

## \*-\*-\*-\*-\* SECTION IX - OTHER REGULATORY CONTROLS

\*-\*-\*-\*-\*

FEDERAL:

Toxic Substance Control Act (TSCA): Ingredients of this product are listed on the EPA/TSCA Inventory of Chemical Substances.

STATE RIGHT-TO-KNOW:

Pennsylvania/New Jersey Right-To-Know (Chemical and CAS No.):

Deionized water 7732-18-5

Diethylene glycol monobutyl ether 112-34-5

Liquefied petroleum gas mixture See below

Propane 74-98-6

n-Butane 106-97-8

## \*-\*-\*-\*-\* SECTION X - TRANSPORTATION REQUIREMENTS (D.O.T. CLASSIFICATION)

\*-\*-\*-\*-\*

Shipping Name: Consumer Commodity Hazard Class: ORM-D

---

NG-- Negligible NA-- Not Applicable NE-- Not Established UN-- Unavailable ND-- Not Determined

While the information set forth herein is believed to be accurate as of the date hereof, the Company makes no warranty or guarantee, express or implied, and disclaims all liability arising out of the use of this information.  
EFFECTIVE DATE: 10/03/01 SUPERCEDES: 3/12/01 PREPARED BY: Ron Cepa